

FLAKE ICE MAKERS with sweet water or seawater Mod.series "CA" complete with cabinet and air motocondensing unit

PRODUCT RANGE FROM 350 TO 4200 KG/24h

- Stainless steel framing ASI 316
- Easy to installation and low operating costs
- Simply connect water and power supply



| MODEL | FT 350 CA | FT 550 CA | FT 800 CA | FT 1200 CA | FT 2000 CA | FT 2800 CA | FT 4000 CA |
|---|-----------|------------|------------|-------------|-------------|-------------|-------------|
| Daily productivity (kg/24h) | 320/380 | 450/570 | 720/870 | 1100/1300 | 1900/2150 | 2500/2900 | 3600/4200 |
| Gear motor (watt) | 90 | 90 | 110 | 110 | 110 | 110 | 120 |
| Condenser | Aria | Aria | Aria | Aria | Aria | Aria | Aria |
| Water consumption (lt/h) | 15 | 24 | 36 | 54 | 89 | 120 | 175 |
| Refrigeration capacity KW (-30°/+ 40°C) | 1,7 | 2,9 | 4,5 | 7,4 | 11,9 | 16,5 | 19,5 |
| Absorbed power KW | 1,7 | 2,3 | 3,6 | 5 | 7,8 | 11,1 | 13,1 |
| Sizes (cm) width x depth x height | 110x69x86 | 115x85x100 | 115x85x100 | 160x110x115 | 160x110x115 | 160x110x115 | 160x120x130 |
| Weight (kg) | 140 | 200 | 250 | 320 | 400 | 500 | 850 |

- FT 350 CA = Standard: 220/1/50 Hz
- FT 550 CA = Standard: 380/3/50 Hz+N (Upon request: FT 500 220/1/50 Hz)
- Refrigerant: 448 A - 449 A
- Ice thickness: 2÷3mm
- Ice temperature: -14÷ -18

STANDARD EQUIPMENT

380/3/50 + N -220/1/50 A. C. stainless steel frame - evaporator - gear reducer - automatic valve gas solenoid - thermostat - probes for water lack - electrical connection terminals

UPON REQUEST

evaporator eletrical resistance - ice conveyor - micro for super-full - stainless steel evaporator jacket saltwater dosing device - water level electroprobe

The 24-hour production index is based on a temperature of 24°C and supply water temperature of 18°C and may vary depending on installation conditions.