

FLAKE ICE MAKERS with sweet water or seawater Model "CA" complete with cabinet and motocondensing unit

PRODUCTION FROM 5200 TO 8100 KG/24h

- Stainless steel framing ASI 316
- Easy to installation and low operating costs
- Simply connect water and power supply
- Possibility to request the machine in two separate blocks (evaporating unit and condensing unit)



MODEL	FT 5600 CA	FT 8000 CA
Daily productivity (kg/24h)	5200/5800	7200/8100
Gear motor (watt)	2x110	2x120
Water consumption (lt/h)	240	335
Refrigeration capacity KW (-30°/+ 40°C)	28	35
Absorbed power KW	21,3	26,8
Sizes (cm) width x depth x height	300x190x170	300x120x185
Weight (kg)	1000	1300

- FT 4000÷8000 = Standard 380/3/50 Hz+N
- Refrigerant: R 448 A - R 449 A
- Ice thickness: 2÷3mm
- Ice temperature: -14÷ -18

STANDARD EQUIPMENT

Stainless steel frame - evaporator - gear reducer - automatic valve
gas solenoid - thermostat - water level control - semi-hermetic moto-compressor - condenser
combined pressure switch - liquid indicator - dehydrating filter - oil separator - liquid separator / heat exchanger
electric board - crankcase heater - speed regulator - oil pressure switch - saltwater dosing device - liquid receiver
UPON REQUEST

liquid injection - evaporator electrical resistance - remote switch-on command - ice conveyor
remote condenser - stainless steel evaporator jacket - electric panel with PLC

The 24-hour production index is based on a temperature of 24°C and supply water temperature of 18°C and may vary depending on installation conditions.