

FLAKE ICE MAKERS with sweet water or seawater Model "CW" modular complete with cabinet and motocondensing unit

PRODUCT RANGE FROM 5200 TO 8100 KG/24h

- Stainless steel framing ASI 316
- Easy to installation and low operating costs
- Pre-arranged for connection to the electrical and water systems
- Possibility to request the machine in two separate blocks (evaporating unit and condensing unit)



MODEL	FT 5600 CW	FT 8000 CW
Daily productivity (kg/24h)	5200/5800	7200/8100
Gear motor (watt)	2x110	2x120
Water consumption (lt/h)	241	291
Condenser water consumption m3/h	7,3	8,6
Refrigeration capacity KW (-30°/+ 40°C)	29000	38700
Absorbed power KW	21,2	24,2
Sizes (cm) width x depth x height	210x130x160	210x130x175
Weight (kg)	1000	1300

- Electrical standards: 380/3/50 +N
- Refrigerant: R 448 A -R 449 A
- Ice thickness: 1,5÷3mm
- Ice temperature: -14÷ -18

STANDARD EQUIPMENT

stainless steel frame freezer - gear reducer - automatic valve - gas solenoid - thermostat - water level control
 semi-hermetic moto-compressor - water condenser - combined pressure switch - liquid indicator
 dehydrating filter - liquid separator / heat exchanger - oil separator - eletric board - crankcase heater
 oil pressure switch (where required by the compressor) - saltwater dosing device - liquid receiver

UPON REQUEST

liquid injection - freezer eletrical resistance - remote condenser - remote switch-on command
 ice conveyer - freezer jacket stainless steel PLC

The 24-hour production index is based on a temperature of 20°C and supply water temperature of 18°C and may vary depending on installation conditions.