

**FLAKE ICE MAKERS with sweet water or seawater  
Mod.series“P” guarded evaporator without  
motocondensing unit**

**PRODUCTION FROM 5200 TO 8100 KG/24h**

- Stainless steel fairing ASI 316
- Easy to installation and low operating costs
- Predisposed for connection to the motocondensing unit



MODEL	FT 5600 P	FT 8000 P
Daily productivity (kg/24h)	5200/5800	7200/8100
Gear motor (watt)	2x110	2x120
Water consumption (lt/h)	240	335
Capacity KW (-30° / + 40°C)	28	35
Sizes (cm) width x depth x height	145x65x120	140x150x85
Weight (kg)	350	520

- Refrigerant: 448A - 449A
- Ice thickness: 2÷3mm
- Ice temperature: -14÷ -18

**STANDARD EQUIPMENT**

380/3/50 + N= stainless steel frame - evaporator - gear reducer - automatic valve  
gas solenoid - thermostat - probes for water lack - electrical connection terminals - connecting collector  
UPON REQUEST  
evaporator eletrical resistance - ice conveyor - micro for super-full - stainless steel evaporator jacket  
saltwater dosing device - water level electroprobe

The 24-hour production index is based on a temperature of 24°C and supply water temperature of 18°C and may vary depending on installation conditions.